

Network Working Group
Request for Comments: 3363
Updates: 2673, 2874
Category: Informational

R. Bush
A. Durand
B. Fink
O. Gudmundsson
T. Hain
Editors
August 2002

Representing Internet Protocol version 6 (IPv6)
Addresses in the Domain Name System (DNS)

Status of this Memo

This memo provides information for the Internet community. It does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2002). All Rights Reserved.

Abstract

This document clarifies and updates the standards status of RFCs that define direct and reverse map of IPv6 addresses in DNS. This document moves the A6 and Bit label specifications to experimental status.

1. Introduction

The IETF had begun the process of standardizing two different address formats for IPv6 addresses AAAA [RFC1886] and A6 [RFC2874] and both are at proposed standard. This had led to confusion and conflicts on which one to deploy. It is important for deployment that any confusion in this area be cleared up, as there is a feeling in the community that having more than one choice will lead to delays in the deployment of IPv6. The goal of this document is to clarify the situation.

This document also discusses issues relating to the usage of Binary Labels [RFC 2673] to support the reverse mapping of IPv6 addresses.

This document is based on extensive technical discussion on various relevant working groups mailing lists and a joint DNSEXT and NGTRANS meeting at the 51st IETF in August 2001. This document attempts to capture the sense of the discussions and reflect them in this document to represent the consensus of the community.

The main arguments and the issues are covered in a separate document [RFC3364] that reflects the current understanding of the issues. This document summarizes the outcome of these discussions.

The issue of the root of reverse IPv6 address map is outside the scope of this document and is covered in a different document [RFC3152].

1.1 Standards Action Taken

This document changes the status of RFCs 2673 and 2874 from Proposed Standard to Experimental.

2. IPv6 Addresses: AAAA RR vs A6 RR

Working group consensus as perceived by the chairs of the DNSEXT and NGTRANS working groups is that:

- a) AAAA records are preferable at the moment for production deployment of IPv6, and
- b) that A6 records have interesting properties that need to be better understood before deployment.
- c) It is not known if the benefits of A6 outweigh the costs and risks.

2.1 Rationale

There are several potential issues with A6 RRs that stem directly from the feature that makes them different from AAAA RRs: the ability to build up addresses via chaining.

Resolving a chain of A6 RRs involves resolving a series of what are nearly-independent queries. Each of these sub-queries takes some non-zero amount of time, unless the answer happens to be in the resolver's local cache already. Other things being equal, we expect that the time it takes to resolve an N-link chain of A6 RRs will be roughly proportional to N. What data we have suggests that users are already impatient with the length of time it takes to resolve A RRs in the IPv4 Internet, which suggests that users are not likely to be patient with significantly longer delays in the IPv6 Internet, but terminating queries prematurely is both a waste of resources and another source of user frustration. Thus, we are forced to conclude that indiscriminate use of long A6 chains is likely to lead to increased user frustration.

The probability of failure during the process of resolving an N-link A6 chain also appears to be roughly proportional to N, since each of the queries involved in resolving an A6 chain has roughly the same probability of failure as a single AAAA query.

Last, several of the most interesting potential applications for A6 RRs involve situations where the prefix name field in the A6 RR points to a target that is not only outside the DNS zone containing the A6 RR, but is administered by a different organization entirely. While pointers out of zone are not a problem per se, experience both with glue RRs and with PTR RRs in the IN-ADDR.ARPA tree suggests that pointers to other organizations are often not maintained properly, perhaps because they're less susceptible to automation than pointers within a single organization would be.

2.2 Recommended Standard Action

Based on the perceived consensus, this document recommends that RFC 1886 stay on standards track and be advanced, while moving RFC 2874 to Experimental status.

3. Bitlabels in the Reverse DNS Tree

RFC 2673 defines a new DNS label type. This was the first new type defined since RFC 1035 [RFC1035]. Since the development of 2673 it has been learned that deployment of a new type is difficult since DNS servers that do not support bitlabels reject queries containing bit labels as being malformed. The community has also indicated that this new label type is not needed for mapping reverse addresses.

3.1 Rationale

The hexadecimal text representation of IPv6 addresses appears to be capable of expressing all of the delegation schemes that we expect to be used in the DNS reverse tree.

3.2 Recommended Standard Action

RFC 2673 standard status is to be changed from Proposed to Experimental. Future standardization of these documents is to be done by the DNSEXT working group or its successor.

4. DNAME in IPv6 Reverse Tree

The issues for DNAME in the reverse mapping tree appears to be closely tied to the need to use fragmented A6 in the main tree: if one is necessary, so is the other, and if one isn't necessary, the other isn't either. Therefore, in moving RFC 2874 to experimental, the intent of this document is that use of DNAME RRs in the reverse tree be deprecated.

5. Acknowledgments

This document is based on input from many members of the various IETF working groups involved in this issues. Special thanks go to the people that prepared reading material for the joint DNSEXT and NGTRANS working group meeting at the 51st IETF in London, Rob Austein, Dan Bernstein, Matt Crawford, Jun-ichiro itojun Hagino, Christian Huitema. Number of other people have made number of comments on mailing lists about this issue including Andrew W. Barclay, Robert Elz, Johan Ihren, Edward Lewis, Bill Manning, Pekka Savola, Paul Vixie.

6. Security Considerations

As this document specifies a course of action, there are no direct security considerations. There is an indirect security impact of the choice, in that the relationship between A6 and DNSSEC is not well understood throughout the community, while the choice of AAAA does leads to a model for use of DNSSEC in IPv6 networks which parallels current IPv4 practice.

7. IANA Considerations

None.

Normative References

- [RFC1035] Mockapetris, P., "Domain Names - Implementation and Specification", STD 13, RFC 1035, November 1987.
- [RFC1886] Thompson, S. and C. Huitema, "DNS Extensions to support IP version 6", RFC 1886, December 1995.
- [RFC2673] Crawford, M., "Binary Labels in the Domain Name System", RFC 2673, August 1999.
- [RFC2874] Crawford, M. and C. Huitema, "DNS Extensions to Support IPv6 Address Aggregation and Renumbering", RFC 2874, July 2000.

[RFC3152] Bush, R., "Delegation of IP6.ARPA", BCP 49, RFC 3152
August 2001.

Informative References

[RFC3364] Austein, R., "Tradeoffs in Domain Name System (DNS)
Support for Internet Protocol version 6 (IPv6)", RFC 3364,
August 2002.

Editors' Addresses

Randy Bush
EMail: randy@psg.com

Alain Durand
EMail: alain.durand@sun.com

Bob Fink
EMail: fink@es.net

Olafur Gudmundsson
EMail: ogud@ogud.com

Tony Hain
EMail: hain@tndh.net

Full Copyright Statement

Copyright (C) The Internet Society (2002). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.